

the two retainers 44, 44 are only added without subjecting the metal elements 32 to a special processing.--

IN THE CLAIMS:

Please amend claims 1 and 2 as follows:

1. (Amended) A belt for a continuously variable transmission, which is wound around a drive pulley and a driven pulley for transmitting a driving force between both the pulleys, the belt comprising a pair of metal ring assemblies each formed of a plurality of endless metal rings laminated one on another, and a large number of metal elements each having a ring slot into which each of the metal ring assemblies are fitted, wherein

an endless resilient member which is deformable radially is disposed between a radially outer edge of each of the ring slots in the metal elements and a radially outer peripheral surface of each of the metal ring assemblies.

2. (Amended) A belt for a continuously variable transmission, which is wound around a drive pulley and a driven pulley for transmitting a driving force between both the pulleys, the belt comprising a metal ring assembly formed of a plurality of endless metal rings laminated one on another, and a large number of metal elements each having a ring slot into which the metal ring assembly is fitted,

wherein an endless resilient member which is deformable radially is disposed between a radially outer edge of the ring slot in the metal element and a radially outer peripheral surface of the metal ring assembly; and,

A2
concl

wherein the peripheral length of the radially inner peripheral surface of the resilient member is set longer than that of the radially outer peripheral surface of the metal ring assembly.

Please add new claims 3-11 as follows:

A3

--3. (New) The belt of claim 1 wherein a clearance is set between the radially inner peripheral surface of the resilient member and the radially outer peripheral surface of the metal ring assembly.

4. (New) The belt of claim 3 wherein the clearance is set at 0.10 mm.

5. (New) The belt of claim 2 wherein a clearance is set between the radially inner peripheral surface of the resilient member and the radially outer peripheral surface of the metal ring assembly.

6. (New) The belt of claim 5 wherein the clearance is set at 0.10 mm.--

7. (New) The belt of claim 3 wherein a further clearance is set between the radially outer edge of each of the ring slots and a radially outer peripheral surface of the associated resilient member.--

8. (New) The belt of claim 7 wherein said further clearance is smaller than said clearance between the radially inner peripheral surface of the resilient member and the radially outer peripheral surface of the metal ring assembly.--

9. (New) The belt of claim 5 wherein a further clearance is set between the radially outer edge of the ring slot and a radially outer peripheral surface of the resilient member.--

10. (New) The belt of claim 9 wherein said further clearance is smaller than said clearance between the radially inner peripheral surface of the resilient member and the radially outer peripheral surface of the metal ring assembly.—

11. (New) A belt for a continuously variable transmission, which is wound around a drive pulley and a driven pulley for transmitting a driving force between both the pulleys, the belt comprising a metal ring assembly formed of a plurality of endless metal rings laminated one on another, and a large number of metal elements each having a ring slot into which the metal ring assembly is fitted,

wherein said metal ring assembly is interposed between the radially outer edge of the ring slot and a saddle face of the metal element constituting a radially inner edge of said ring slot, and

wherein an endless resilient member which is deformable radially is disposed between said radially outer edge of the ring slot and a radially outer peripheral surface of the metal ring assembly.

REMARKS

Claims 1-11 are pending in this application. By this Amendment, claims 1 and 2 are amended and new claims 3-11 are added. No new matter is added.

Section 102 Rejection

The Office Action rejects claim 1-2 as being anticipated by Sekine et al. (U.S. Patent No. 5,123,880). This rejection is traversed as it may apply to the amended claims.